

[ CE Technical Data Sheet ]

## Firestone PondGard™ CE

### Description

The Firestone PondGard™ CE membrane is a non reinforced black single-ply synthetic rubber membrane made of Ethylene-Propylene-Diene Terpolymer (EPDM) with a nominal thickness of 1 mm.

### Use:

The membrane is specifically used as a waterproofing membrane in decorative pond applications.

### Characteristics:

Property	Standard	Declared Mean Value	Tolerance
Tensile strength (MD/CD)	ISO R 527	9 N/mm <sup>2</sup>	-1 N/mm <sup>2</sup>
Resistance to static puncture	EN ISO 12236	0.6 kN	-0.1kN
Water permeability (Liquid tightness)	EN 14150	3.0 10 <sup>-6</sup> m <sup>3</sup> /m <sup>2</sup> d	±10 <sup>-6</sup> m <sup>3</sup> /m <sup>2</sup> d
Durability - weathering (25y)	EN 12224	pass	
Durability - oxidation	EN 14575	pass	
Durability - environmental stress cracking	ASTM D 5397-99	NPD	

Manufacturer's declared values in accordance with EN 13361 and EN 13362.

Issue 2, 30 January 2009



1725-CPD-M0003  
09

Please check [www.firestonebpe.com](http://www.firestonebpe.com) for updates